


Product selection:

Part no.		Profile	Conduit size		rec. fitting thread size		Dimensions in mm (nom.)			Weight	Packing unit
black	grey	T/G	NW	metric	PG	metric	d1	d2	stat. R	kg/100 m	metre
VAMT-07B	VAMT-07S	T	7	10	7	M12x1.5	6.6	10.0	20	2.5	50
VAMT-10B	VAMT-10S	T	10	12	9	M12x1.5	9.6	12.8	25	3.3	50
VAMT-12B	VAMT-12S	T	12	16	11	M16x1.5	12.0	15.6	30	4.4	50
VAMT-17B	VAMT-17S	T	17	20	16	M20x1.5	16.6	21.1	40	7.5	50
VAMT-23B	VAMT-23S	T	23	25	21	M25x1.5	23.0	28.4	50	12.5	50
VAMT-29B	VAMT-29S	T	29	32	29	M32x1.5	28.7	34.5	60	16.0	50
VAMG-17B	VAMG-17S	G	17	20	16	M20x1.5	15.5	21.1	45	8.0	50
VAMG-23B	VAMG-23S	G	23	25	21	M25x1.5	21.6	28.4	60	12.5	50
VAMG-29B	VAMG-29S	G	29	32	29	M32x1.5	27.6	34.5	70	16.0	50
VAMG-36B	VAMG-36S	G	36	40	36	M40x1.5	35.8	42.4	85	20.5	30
VAMG-48B	VAMG-48S	G	48	50	48	M50x1.5	46.6	54.5	110	27.0	30

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



stat. R. = min. bending radius for static (fixed) installation

Mechanical Properties:	Value:	Test parameters:	Test method:
Impact strength	> 13 J	(+23°C)	PMA DO 9.21-4330
	class 3, > 2 J	(-45°C)	IEC EN 61386
	class 4, > 6 J	(-15°C)	IEC EN 61386
	class 5, > 20 J	(+23°C)	IEC EN 61386
Compression strength	> 350 N	(50 x 50 mm)	PMA DO 9.21-4320
	> 700 N	(100 x 100 mm)	PMA DO 9.21-4320
	class 3		IEC EN 61386
Resistance to fatigue	> 10'000 cycles		PMA DO 9.21-4420
	> 20'000 cycles		PMA DO 9.21-4425
	> 5'000 cycles	(-5°C)	IEC EN 61386-23
	pliable	(-45°C)	IEC EN 61386-22
Pull-out resistance conduit - fitting series			
PMAFIX Pro			PMA DO 9.21-4610
PMAFIX IP68	> 500 N		PMA DO 9.21-4610
PMAFIX IP66	> 450 N		PMA DO 9.21-4610
PMAFIX Pro, PMAFIX IP66 & IP68	class 2		IEC EN 61386

Note: Testing at 23°C, 50% r.h., conduit nominal width 17, unless otherwise stated

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	-40 ... +105°C		PMA DO 9.21-4510
Upper application temperature	+120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+160°C	(168 h)	PMA DO 9.21-4360
Application temperature range	-45 ... +105°C		IEC EN 61386

Fire safety properties:	Value:	Test parameters:	Test method:
Fire performance	non flame-propagating		IEC EN 61386
Fire hazard level	HL3		EN 45545-2 (R22)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 150 Ds max.		EN ISO 5659-2 (25 kW/m ²)
Toxicity	< 0.75 CIT _{NLP}		NF X 70-100-1/-2: (600°C)
Fire hazard level	HL3		EN 45545-2 (R23)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 300 Ds max.		EN ISO 5659-2 (25 kW/m ²)
Toxicity	< 1.5 CIT _{NLP}		NF X 70-100-1/-2: (600°C)
Fire performance NFPA 130:			NFPA 130
- Flammability	compliant		ASTM E 162
- Smoke density	compliant		ASTM E 662
Heat and visible smoke	28.51 MJ/kg		ASTM E 1354
Smoke emission toxicity	compliant		Bombardier SMP 800-C
Smoke emission toxicity	compliant		Boeing BSS 7239

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

